

FITMENT AND BOTTLE

Background of the Invention

Heavy duty liquid detergent products have grown in popularity over recent years. The sale of such products in specialized dispensing packages, usually including a combined measuring cup/closure, and a drainback fitment/spout has aided the consumers in the use of such products.

While drainback containers have enhanced the convenience of the use of heavy duty liquid detergents and other products, still some problems exist. Many of the containers include fitments which extend well below the top of the container finish into the bottle. The problem which this presents is that it is sometimes difficult to pour out from the container the last remnants of product since product becomes entrapped between the fitment and the container finish when the bottle is in the inverted, pouring position. This is particularly a problem for "see-through" containers, which can be expected to maximize consumer frustration with the inability to utilize the entire product present within the container.

Barker et al., U.S. Patent No. 4,550,862 discloses a dispenser package which includes a transition collar having an extended pour spout and a transverse partition with a drain to collect and return residual liquid to the container. A measuring cup has an open mouth with threads on its exterior to attach to the cup on the interior of the transition collar. The measuring cup acts as a closure for the package. The bottle finish has external threads that mate with internal threads on the transition collar.

Muckenfuhs et al., U.S. Patent No. 4,696,416 is directed to a package similar to that of Barker et al. except that a drip concentrating member is present in the lowermost surface of the drainback partition.

Davidson et al., U.S. Patent No. 5,108,009 discloses a package having a spout-containing fitment wherein external threads on the package finish cooperate with internal threads on a closure/measuring cup. The Davidson et al. bottle includes a locking circumferential ridge on an inner peripheral surface of the upper end portion of the bottle finish (see Figs. 9 and 10), which retains the fitment.

The Davidson et al. design is embodied in heavy-duty liquid detergent containers sold by Lever Brothers Company for products such as Surf and Wisk® detergents, sold for over one year in the U.S.. The fitment of these commercially available containers includes, in addition to a drainback opening, an opening in the sidewall of the fitment to permit liquid entrapped between the wall of the fitment and the container finish to exit the container. While this arrangement has improved the ability to dispense more of the product, there is still a need to minimize further the loss of product to the consumer when liquid is trapped between the wall of the fitment and the finish of the container.

CA 2225949 discloses a bottle having a fitment with a spout. It is said that more than one product exit aperture may be present and that the product exit aperture also serves as a vent hole. The product exit aperture is said to be located high enough in the fitment wall such that at least a portion of liquid trapped when the bottle is turned upside down can escape. It may be positioned halfway down the wall of the fitment, or one quarter of the way down or three quarters of the way down or elsewhere.

Kittscher, U.S. Patent No. 4,773,560 discloses a measuring cup closure for a container. The closure has a spout part which is placeable in the container opening, a pouring spout and an outer ring formed integrally around the base of the spout part. The closure also includes a measuring cup. In order to ensure that product draining from the measuring cup after it has been used is able to flow back into the interior of the container, an outlet preferably in the form of a slot 17 extends substantially parallel to the axis 1 of the container opening 2 is provided in the outer ring 8 at the base 15 of the outer ring or at the lowest point of the region 16 between the pouring spout 7 and its outer ring 8. A thread gap 22 at the outer end of outer screw thread 4 forms a stop for alignment of the spout part.

The Kittscher patent also states, more generally, that when the spout part projects into the container as is preferably the case, a slot extending substantially parallel to the axis of the container opening is provided in the outer ring of the spout part opposite the pouring side of the spout. The remaining product can be poured out through this slot when the container is held upside down.

Ekkert et al., U.S. Patent No. 5,435,467 is directed to a container having an externally threaded finish which mates with an internally threaded finish of a closure. A fitment having a radially extending flange is inserted within the mouth of the container and the radially extending flange rests upon the top of the finish. The arrangement is such that the amount of residual contents left within the container is said to be diminished. The illustrated spout fitment appears to have substantial areas open for product to flow through, relative to the area defined by the outer spout wall.

Other bottle patents include Li, U.S. Patent No. 4,706,829, Burt, U.S. Patent No. 3,217,935, Iida, U.S. Patent No. 4,298,145 and Odet, U.S. Patent No. 4,830,234.

The following discloses bottles and/or spouts: Bavegems, U.S. Patent No. 5,131,566, Moore, U.S. Patent No. 5,251,788, Haga et al., U.S. Patent No. 4,890,770, Haffner et al., U.S. Patent No. 5,462,202, Fuchs et al., U.S. Patent No. 4,917,269, Moore et al., U.S. Patent No. 5,058,772, and Reiber et al., U.S. Patent No. 4,671,421.

Summary of the Invention

The present invention is directed to a fitment and a bottle body and to the container including fitment, bottle body and/or closure which can minimize the amount of residual product which remains in the container once its contents have been substantially depleted. The fitment of the invention comprises an outer wall, a bottom wall and a pour spout extending upwardly from the bottom wall. The outer wall includes a vent hole which also acts as a product exit aperture, preferably spaced from the bottom wall when the bottle is nearly fully inverted. More preferably, at least 40% of the area of the product exit aperture is contained within an upper half of the outer wall, still more preferably at least 50% of the area, more preferably at least 70% of the area and most preferably at least 80% of the area is contained within the upper half of the outer wall. If desired, additional product exit apertures may be present. Generally, it will be desirable that the bottom wall itself includes one or more product drainage apertures.

In accordance with the invention, a bottle body is provided which extends upwardly from a base and ends in a bottle finish. The finish includes one or more inner locking surfaces disposed to abut the outer wall of the fitment and an inner channel in one or more of the locking surfaces which is positioned to lead product which is disposed between the outer wall of the fitment and inner aspects of the finish when the container is inverted, to the product exit aperture and then out of the bottle and or directly out of the bottle. In one embodiment, the channel extends to the level of the product exit aperture, e.g. to the level of the top end (when the bottle is inverted) of the product exit aperture. Alternatively, the channels in the locking surfaces can extend through the locking surfaces to the exterior of the container. By use of a channel, it is possible for most of the last remnants of product to be poured from the container when it is in an inverted position, notwithstanding the abutting locking surface(s) on the finish which would otherwise tend to block or severely limit egress of residual product from the container. Since the fit between the locking surface(s) and the outer fitment base is not liquid-tight, the channel is particularly useful for promoting egress from the container of product trapped, or which would otherwise be trapped, between the locking surface(s) and the outer wall of the fitment.

Both the finish channel and the product exit aperture may advantageously be tapered at an upper end to promote egress of the product from the container. The container of the invention is especially suitable for containing or for housing liquid consumer products such as heavy-duty liquid detergents and liquid fabric softeners.

In alternative embodiments, the channel may instead be present in the outer wall of the fitment and may also be tapered.

In accordance with another aspect of the invention, the threads on the outside of the container finish may be interrupted along a vertical line parallel to the longitudinal axis of the container to make room for a linear protuberance on the outside of the finish which may be formed during formation of the channel in the inside of the finish. The protuberance is preferably shallow to avoid interference with the cap threads. The protuberance may be situated at the parting line of the bottle.

For a more complete understanding of the above and other features and advantages of the invention, reference should be made to the following detailed description of the preferred embodiments and to the accompanying drawings.

Brief Description of the Drawings

Fig. 1 is a front elevational view of the fitment of the invention.

Fig. 2 is a rear perspective view of the fitment of the invention.

Fig. 3 is a perspective view of the container of the invention.

Fig. 4 is a cross section along the lines 4-4 of Fig. 3.

Fig. 5 is a front perspective view of the container with the fitment removed.

Fig. 6 is a cross section along the lines 6-6 of Fig. 3.

Fig. 7 is the same view as Fig. 5, but of an alternate embodiment.

Fig. 8 is a rear perspective view of an alternate fitment.

Fig. 9 is the same view as Fig. 8, except that a further alternate embodiment is illustrated.

Fig. 10 is the same view as Fig. 9 except that a still further alternate embodiment is illustrated.

Fig. 11 is a cross section similar to Fig. 4, except that the closure and extraneous portions of the container have been removed.

Fig. 12 is an enlarged version of a portion of Fig. 11.

Fig. 13 is an enlarged version of a portion of Fig. 6

Detailed Description of the Invention

Referring now particularly to Figures 3 and 4, there is shown a container 2 including a bottle 6 having an integral handle 8 and a neck 10. The container 2 also includes a drainback fitment 14. Fastened to the top of the container 2, as viewed in Figure 3, there is a closure or cap 12. All of the foregoing components are preferably molded from a resilient flexible plastic material. The materials may be selected so that the plastic from which the drainback fitment 14 is molded is softer than the materials from which the bottle 6 and closure 12 are formed. Alternatively, the drainback fitment may be made of a material of comparable hardness to that of the polypropylene of which the closure is generally made, e.g., LDPE (or HDPE).

The drainback fitment has an outer, frustoconical wall portion 16 which gradually tapers downwardly and inwardly and is received within the neck 10 of the bottle 6. The wall portion 16 terminates at its upper end in an annular rim 19. Rim 19 is generally flat.

The surface of the rim turns downwardly and inwardly to form the outer wall 24 of a circumferential well 26 surrounding a generally frustoconical, eccentrically positioned (off-center) spout 36, the lower periphery of which forms the inner wall 28 of the circumferential well 26. Between the outer wall 24 and inner wall 28 of

the circumferential well 26 there is a sloping floor, bottom wall 30. The outer surface of wall 16 optionally includes a retaining ring which is spaced from and generally concentric with rim 19. Wall 16 includes a product exit aperture 412 (or drain port) located above and spaced from product drainage aperture 32 in bottom wall 30. Product exit aperture 412 serves to permit residual amounts of product caught between the finish or neck of the container and the outer wall of the fitment when the bottom is in the inverted (pouring) position to exit the container through the fitment. Product exit aperture 412 is tapered at 430 to promote egress of the product. The basic features of the fitment, bottle finish and closure are as shown in Fig. 9 of Davidson et al. U.S. Patent No. 5,108,009, the disclosure of which patent is hereby incorporated by reference herein. An appropriate product drainage aperture is illustrated in more detail in Fig. 3 of Davidson et al.

The product drainage aperture or notch 32 preferably comprises a substantially rectangular notch formed in the lowest and widest portion of the floor 30 and is desirably in alignment with a longitudinal slot 34 which extends from the top of the rear of the spout. While the longitudinal slot may extend to the notch 32 and merge therewith, if desired, the slot may extend only approximately halfway down the length of the spout.

The spout may include projections to keep the fitments separated during stacking. Such projections may also serve to prevent rotation of the spouts during stacking when combined with lugs (not shown) depending from the bottom of the fitment and situated so that they block radial movement of the stacking projections on the next lower fitment when the fitments are stacked.

Notch 32 and longitudinal slot 34 provide a path for residual liquid remaining on the spout 36 or closure 12 to drain back into the bottle 6 either directly or via the downwardly sloping floor 30 of the circumferential well 26 under the force of gravity when the container 2 is in an upright position.

Fitment 14 is secured to bottle finish 68 by a friction fit and is vertically positioned by resting on an inner bottle ledge. Bottle finish 68 includes an annular mouth 70, and a locking ridge 72. The finish includes external threads 74. The fitment is inserted into the bottle by forcing it through the opening at the bottle mouth and pushing it until annular rim 19 of the fitment is situated upon or above locking ridge 72. If rim 19 is above locking ridge 72, preferably it is immediately above. In this position, the distal end of the annular rim will be adjacent to bottle mouth 70. Optionally, a retaining ring of the fitment helps to retain the fitment in position by abutting the lower aspects of locking ridge 72.

As seen in Figs. 5 and 6, in accordance with the invention, channel 410 extends through locking ridge 72 to permit egress of residual amounts of liquid product from the container from between the fitment and the finish through the channel and out the container. If desired or necessary to facilitate egress of product, rim 19 may include a discontinuity 520 (Fig. 8) aligned with channel 410. Alternatively, as seen in the alternative embodiments of Fig. 7, 11 and 12, the finish includes a second locking ridge 71 having channel 411 extending through it. Product trapped between the finish 68 and outer wall 16 of the fitment travels through channel 411 and exits through the product exit aperture or continues through to channel 410 and exits the container through discontinuity or channel 520 in rim 19. The optional tapering at the upper ends 440, 441 of channels 410, 411 promotes controlled exit of the product from the container. Where the optional

retaining ring is present on the fitment outer wall at the level of the product exit aperture, the ring may be interrupted at the level of the aperture.

Further alternative embodiments are illustrated in Figs. 9 and 10 wherein channels 410a and 410b are formed in the outer fitment walls and extend respectively from the upper end of the product exit aperture to the top of the fitment (Fig. 9) and from the bottom of the fitment wall 16b to the bottom of the product exit aperture. Rim 19a (Fig. 9) is interrupted at 550 to promote egress of fluid from an inverted container.

If desired, the spout 36 may be provided with an anti-drip lip. Also, it may be desirable to provide the spout with a V-shaped pouring angle for improved control of pouring of the product.

The drainback fitment 14 may be formed from a thermoplastic such as high density polyethylene. Or it may be made of a polyethylene which is a product of a 50:50 blend of a high density resin and a low density resin. The high density resin can be U.S.I. LS 506 or a similar resin. The low density resin can be U.S.I. LS 208 or the like. Instead of a mix of resins, a low density polyethylene such U.S.I. 241 or even a harder material such as polypropylene may be used to form the fitment. Other plastic resins having chemical and physical properties similar to the aforementioned resins can be used in fabricating the drainback fitment 14.

Preferably, the container of the invention provides the spout and drainback area in the form of the above described fitment, separate from the body of the bottle. In the described preferred embodiment, the fitment snaps into the container finish so that a friction fit is obtained between the outer wall of the fitment and the

locking ridge on the inside of the container finish. A fitment may also be provided in other ways, eg it may be applied by spin welding, or by hot melt adhesive or by the EMABOND system. An internally threaded finish may be combined with an externally threaded closure.

The EMABOND system employs a thermoplastic gasket impregnated with metal particles. When the gasket is in position (between a sealing area ridge of the fitment and inside bottle neck ledge), a sealing unit with an electro-magnetic force presses down on the fitment and heats up the metal particles, thereby melting the plastic gasket, and the compression welds the two components together with a leak-proof seal.

It is also contemplated that some of the embodiments may be in the form of refill bottles which contain a plain screw cap and no spout but which are capable of receiving a transferable spout and self draining closure.

The closure 12 has a closed end 38 at its top which is merged at its circumference with a downwardly extending inner circumferential wall 46 having a surface onto which there are integrally molded gripping teeth 42 biased to present greater friction to the hand when the closure 12 is rotated counterclockwise to loosen it than when it is rotated clockwise for tightening. Alternatively, other gripping means, such as vertical ribbings may be employed.

The inner circumferential wall 46 is concentric with and spaced from an outer circumferential wall 40. Inner circumferential wall 46 extends downwardly beyond the length of the outer circumferential wall 40. The inner circumferential wall 46 and the undersurface of the closed end 38 form a cup for measuring the

contents of the container 2 as it is poured from the bottle 6. A fill line can be molded into the inner circumference of the inner wall if desired. Internal vertical lines closely spaced together can be provided to enhance the visibility of the fill line.

The outer circumferential wall 40 and inner circumferential wall 46 are connected by a web 48 so that a downwardly facing (when the closure 12 is fastened to the bottle 6) channel is defined between the inner circumferential wall 46 and the outer circumferential wall 40. The channel is optionally lined with a liner preferably made of a resilient, polymeric material. However, it is preferred that the channel be linerless. The channel in cooperation with the frustoconical wall portion 16 and optional liner serves as a trap for preventing residual contents of the container 2 from migrating to the junction of the closure 12 and neck 10 of the bottle 6. If desired, the liner may be omitted.

Complimentary fastener means in the form of threads are provided on the closure 12 and neck 10 of the bottle 6 at their juncture. The closure 12 has internal threads 50 which mate with external threads 74 on the finish 68 of the bottle. As the closure 12 is threaded onto the neck 10 of the bottle 6, the liner, if present, engages the mouth 70 of the bottle 6 thereby sealing the bottle to prevent leakage of the contents from the container. When the liner is omitted, the top of the channel seals against the mouth 70 of the bottle. The presence of the fitment rim below the top of the finish permits the closure (or the liner of the closure) to form a seal at one circumferential location at the top of the finish. If the fitment rim extended over the top of the fitment there would be two areas for liquid product to escape through the seal, above and below the rim of the fitment.

The inside of the land of the bottle may be beveled to assist in sealing. The bevel imparts to the top of the mouth a sharp point from which the inner wall of the mouth slants inwardly. The outer wall of the mouth is disposed generally vertically. Whether the closure is on or off, the friction fit of fitment 14 against locking ridge 72 within the bottle finish 68 impedes escape of the product except through the spout, the drainage aperture, the product exit aperture or the channel. When the closure is screwed closed, product which has exited bottle 6 through the spout, drainage aperture, the channel or the product exit aperture is contained within container 2 by the closure.

As is apparent from Figure 4, except for the spout, fitment 14 is wholly contained within the bottle 6. The entire outer wall 16 is situated below the mouth 70 of this bottle.

Although the fitment herein has been described as having a single product exit aperture, a plurality of apertures, e.g., 450 and 452, may be utilized.

In addition to serving to permit use of the last remnants of the product, the product drainage aperture also serves as a vent hole as well. As such, it permits air to enter the container as product leaves through the spout.

The product exit aperture may assume any shape and size suitable for permitting exit of at least a portion of the last fraction of product trapped between the outside of the fitment and the wall of the bottle, e.g. triangular, rectangular or square, or may take the form of a slit. Preferably, the exit aperture is of a size and shape suitable for venting, as well. The product exit aperture is located high enough in the fitment wall such that at least a portion of liquid trapped when the

bottle is turned upside down can escape. The product exit aperture is illustrated herein as occupying the middle half of the height of the fitment outer wall, and as being positioned approximately halfway down the wall of the fitment, although it may be located one quarter of the way down or three quarters of the way down or elsewhere, depending on the dimensions of the container.

While certain features such as the annular rim and the retaining ring have been illustrated and/or described as extending 360 degrees around the circumference of the fitment, it will be apparent that such will not always be necessary in order that their functions be fulfilled in accordance with the invention. For instance, the annular rim may be replaced by other stopping means and the retaining rim may be replaced by other retaining means. Stopping means refers to the annular rim and equivalent structures even in fitments and containers wherein the friction fit between the fitment wall 16 and the locking ridge 72 is sufficient to prevent the entire fitment from being pushed through and into the bottle.

The closure may be formed of a harder material than that used in the drainback fitment 14. In the preferred embodiment of the invention, the plastic material from which the closure 12 is molded is a homopolymer or copolymer polypropylene such as that sold by Phillips Petroleum Company under the designation Phillips HLV 120-01.

The bottle 6 also may be formed of a material that is harder than the material employed in the drainback fitment 14. Alternately, the fitment may be formed of a harder material, as where the fitment is fabricated from polypropylene. Materials from which the bottle may be fabricated include high density polyethylene. Or, another resin sold by U.S.I. under the designation .955 density,

OI-388-2, is a suitable material. Other materials exhibiting similar chemical and physical properties can be substituted. Preferably, however in accordance with certain embodiments of the invention, the bottle is made from multiple layers.

The bottle of the invention preferably is made of at least one resin layer, especially the inner layer, which possesses a good stress crack resistance, as determined according to ASTM D-1693-95. That is, the layer preferably has at least 75 hours, and more preferably at least 100 hours, most preferably at least 300 hours stress crack resistance under that test. Good stress crack resistance is promoted by the selection of resins having an appropriate distribution of chain lengths, especially distributions favoring long chain lengths. Stress crack resistance is important to the ability of the package to contain effectively its contents for prolonged periods of time on the shelf or in the consumer's cupboard. Polymer layers which have a lower MI (lower melt index) promote stress crack resistance, since they tend to have longer molecular chain lengths, and impact resistance, as well.

Preferably, the container also possesses a good drop strength resistance so that a water filled bottle will survive at least one 3-foot drop onto its base. The drop strength can be important to assure that the container can withstand the travails of packing, shipment, and use and storage by the consumer.

The finished end or body of the bottle is preferably lightweighted. That is, the finished end or body is made of a material which is lighter in weight than standard materials from which heavy duty liquid detergent bottles are made. This permits less material to be used and results in less material to be disposed of after the contents of the bottle have been consumed. A lightweight bottle is described in

Giblin et al., Serial No. 08/777,641, the disclosure of which is incorporated by reference herein.

It should be understood, of course, that the specific forms of the invention herein illustrated and described are intended to be representative only, as certain changes may be made therein without departing from the clear teachings of the disclosure. Accordingly, reference should be made to the following appended claims in determining the full scope of the invention.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217